

EnduStep® - Mobile Work Platform Ladder

Heavy duty / Professional use

- Modular structure made out of Aluminum EnduRail Structural fittings & Extrusions.
- Heavy Duty MS Powder Coated Base Frame with 4" Castor wheel with break - 2 nos. fix and 2 nos. Swivel type
- Wide platform – 600 mm X 600 mm / Customized size
- 100 mm wide aluminum extruded anti slippery steps.
- 250 mm height between two steps.
- Platform Railing 950 mm high
- Toe Guard 150 mm wide
- Heavy duty Rung Railing (Optional)
- Screw jack with Stabilizer arm (Optional)
- Self-Closing Safety Gate (Single leaf / double leaf - Optional)
- Load Capacity : 150 kg.



Model	Platform Height mm	Working Height mm	Platform W X D mm	Overall Base W X D mm **
ES 04	1200	3000	600*600	750*1500
ES 05	1450	3250	600*600	750*1675
ES 06	1700	3500	600*600	750*1850
ES 07	1950	3750	600*600	750*2025
ES 08*	2200	4000	600*600	750*2200
ES 09*	2450	4250	600*600	750*2375
ES 10*	2950	4250	700*700	850*2475

*Outriggers with screw jack is recommended for better stability.

**approximate dimension without outriggers and railing

- No rights can be derived from copy, text pertaining to illustration or samples. Continuous process improvement results Technical data subject to change in material, parts, composition, design, version, color etc. even without notice.