

## MARK SAFETY APPLIANCES

Regd. Office and Warehouse:

Plot No. 92, 93, Shah Industrial Park-3 at Kotambi, Pin Code 391510, Vadodara-Halol Highway, Dist. Vadodara, Gujarat, India.

GST No: 24AABPZ7907Q1ZW MSME No: UDYAM-GJ-24-0020651

02668 299065, 098797 79661 info@marksafety.com

## YT-1200H-WH

**Diffusion Gas Detector** 

## **Product overview**

YT-1200H-WHseries gas detector is a kind of mini size, low cost and high accuracy portable multi gas detector. Easy to operate, comprehensive functions, can measure toxic gases, flammable gases and oxygen gases, etcin hazardous environments. The detector is with back clip, protected by silicone case, suitarble f different kinds of situations.



- Equipped with standard event logging (100 records), the record can be checked on the device
- Smart and lightweight design makes it comfortable to wear
- LCD dot matrix display
- One press to restore factory settings
- Ultra-high buzzer alarm sound, alarm with sound, light and vibration at the same time
- Optional Data logging function, the data can be exported to PC through software we provide
- · Large capacity rechargeable battery, work continuously for a long time
- With alligator clip, convenient to take along
- Strong and durable plastics housing, exquisite and comfortable in touching





## **Technical parameters**

Gas Detected:  O2. CO. H2S. EX is the standard gas combon other combine can be specified  Detection Principle:  Diffusion  Measure range:  Specified according to application	oine,
·	
Measure range: Specified according to application	
opeomed according to application	
Resolution: Specified according to application	
<b>Precision:</b> <1-5% F.S	
Unit: ppm, mg/m3, %VOL, %LEL	
Display: Monochrome dot matrix 128*128 LCD graphic of	display.
Backlight: Time of backlight is settable, when alarm the backlight will be auto on	
<b>Data Logging:</b> 100000 readings. Interval time ranges from 10-seconds are settable. (Optional function)	3600
<b>Event logging:</b> 100 event records can be checked on device	
Language: Chinese/English	
Alarm type: sound, light, vibration	
Battery: 3.7V rechargeable lithium battery, with capaci of 2500mAh	У
Working Time: 14h continuously (common 4 gases) 200h(without LEL sensor)	
Charger: Travel charger. Charging time: 4~6h	
Explosion-proof grade:	
Protection grade: IP65	
Working temperature: $10^{\circ}\text{C} \sim 50^{\circ}\text{C}$	
Working humidity: 15-95%RH	
Housing Material: ABS+ leather case	
<b>Dimension:</b> 131*83*35mm (length*width*height)	
Weight: 240g	